

Impact wrench 3/4"

D322831 / SGS 1700

Product Information Sheet



Technical Data	D322831
Base unit number	T400068
Square drive	3/4"
Air consumption	9,1 l/s
Maximum pressure	6,3 bar
Torque	1.625 Nm
Breakaway torque	2.978 Nm
Speed	5.500 min ⁻¹
Sound pressure level L _{PA 1 m} (at a distance of 1 m) as per EN ISO 15744, part 20	90 dB(A)
Vibration as per EN ISO 28927-2	4,8 m/s ²
Overall dimensions W x D x H	214 x 84 x 266 mm
Weight	3,7 kg
Date	11.02.13 / knoc

Product description

Fact Sheet

Top Performer

- For truck workshops and truck tyre services
- Particularly powerful impact screwdriver due to release torque of 2978 Nm
- Superb power to weight ratio with only 3,7 kg
- Avoidance of pressure points due to ergonomic handle design
- Save and pleasant guiding of the device due to optimal centre of gravity
- Patented twin-hammer clutch, extremely robust und powerful
- EC conformity according to 2006/42/EC; DIN EN ISO 11148-6

Impact wrench 3/4"

D322831 / SGS 1700

Product Information Sheet



Outstanding Balance

Save and comfortable guidance because of optimized centre of gravity

Efficient working

By one-hand forward-/backward-switch

Soft start

Sensitive operation due to controllable trigger

Ergonomic handle design

Avoidance of pressure points on the hand-arm system



Maximum comfort and control

Convex curved profile for a comfortable hand rest

Light

With 3,7 kg composite housing

Economic air consumption

Efficient 3-step torque regulation for different applications

Powerful

Twin-hammer clutch provides high performance with low wear

Exceptionally quiet

Only 90 dB(A) noise level

Further information

Scope of delivery

Cardboard with plug nipple and manual

Warranty

12 months for professional industrial use
24 months for private use only
36 months if registered online