

# CompactMaster 155-8-6 WOF Base A202003

Product specification sheet



Technical Data	A202003
Air displacement	150 l/min
Max. free air delivery	70 l/min
Max. pressure	8 bar
Cylinder/Stage	1/1
Tank capacity	6 l
Voltage	230 Volt/50 Hz
Motor output	1,1 kW
Drive	2.450 min <sup>-1</sup>
Sound pressure level	90 dB(A)
Dimensions(WxDxH)	310x380x270 mm
Weight	10 Kg

## Product description

### Fact Sheet

- Oilfree, mobile, direct driven one cylinder piston compressor
- For applications up to 8 bar
- Extremely handy compressor due to compact and lightweight design
- Equipped with pressure reducer and two pressure gauges for measuring tank and outlet pressure as well as quick release coupling
- Applications: smaller sized staple and nail guns, blow-out guns, cartridge guns, grease guns and rivet guns

# CompactMaster 155-8-6 WOF Base A202003

## Product specification sheet



**extremely handy** due to lightweight design and ergonomic handle

**simple operation** because pressure reducer and quick release coupling are centrally fitted

**cable winder** prevents wire kinking and allows safe carrying

oil free aggregate is **very low-maintenance**

stable stand due to rubber feet and compact design **prevents damage during transport**

**straightforward maintenance** thanks to easily accessible drain valve

**reduced noise level** provides a comfortable working environment



**at a glance overview** - easy to read tank and outlet pressure

### Further information

Operates fully automatically

Equipped with unloader pressure switch

Scope of delivery

Instruction manual

Anti-corrosion warranty on the compressed air tank

5 years