

Stapler KLG 80-16 D200091

Product specification sheet



Technical Data	D200091
Trip mechanism	single shot
Air consumption per shot	0,3 l per shot
Type of staplers	Type 80
Stapler length	4-16 mm
Stapler crown width	12,8 mm
Stapler wire diameter	0,7 x 0,9 mm
Magazine capacity (number of staplers)	157
Operating pressure	4-7 bar
Vibration value	1,85 m/s ²
Sound pressure level (LPA)	84 dB (A)
Sound power level (LWA)	97 dB (A)
Dimensions (WxDxH)	237x43x153
Weight	0,87 kg

Product description

Fact Sheet

- Users: carpenters, interior designers, upholsterers
- Perfect for mounting of films, tissues, leather, insulating materials, carpets, panelling
- Extra light and handy housing
- Two stage trigger prevents accidental firing of staples
- Bottom loading magazine allows quick and easy reloading
- Can be used in difficult to access locations

Stapler KLG 80-16

D200091

Product specification sheet



Rubber grip
absorbs shock
and vibration and
insulates against
cold

**Two stage safety
trigger** avoids
unintentional firing



**Direction of
exhaust air away
from the
operator** which
minimizes
contamination of
the work piece and
noise

Easy troubleshooting
due to functional
magazine rack with
easy access to remove
any blockages and
obstructions

**Bottom loading
magazine** for fast
reloading

Long nose for
using in difficult to
access locations

**Lighter and
compact stapler**
which is less tiring
to use if a large
amount of stapling
is required

Further information

Scope of delivery

Delivered in cardboard box with lubricant oil, hex wrench and instruction manual

Warranty

36 months when registered online
24 months for private (non-commercial) use
12 months for industrial use