

# UNM 660-10-90 D A715000

Product specification sheet



Technical Data	A715000
Air displacement	660 l/min
Max. free air delivery	520 l/min
Max. pressure	10 bar
Cylinder/Stage	2/2
Tank capacity	90 l
Voltage	400 Volt/50 Hz
Motor output	4,0 kW
Drive	1000 min <sup>-1</sup>
Noise level	97dB(A)
Dimensions(WxDxH)	1110x495x1000 mm
Weight	102 kg

## Product description

### Fact Sheet

- Compressor is easily moveable due to caster wheels and extra long handle
- Mobile piston compressor with V-belt drive
- For applications up to 10 bar
- High quality performing compressor is perfect for professional use
- Equipped with filter pressure reducer
- Application: Using impact wrenches, ratchet screwdrivers, pneumatic screw drivers, drills, grinders, saws, rivet guns, grease guns, needle scalers, chipping hammers, smaller sized staple and nail guns, paint spraying guns, shot blasting guns, cartridge guns, blow-out guns and air tyre inflators

# UNM 660-10-90 D A715000

## Product specification sheet



**Silent run and perfect cooling** due to approved cooling air flow and approved aggregate with V-belt drive

**Ergonomic extra long carrying handle** perfectly fitted and extra lifting handle on the tank

**Precise working** due to filter pressure reducer for controlling the air pressure perfectly

**High flexibility** is provided by 2 m cable length

**Convenient working** due to quick release coupling

**Long service life** thanks to the 10 years anti-corrosion warranty on the compressed air tank

**Excellent working comfort** thanks to clearly arranged pressure gauges for measuring tank and outlet pressure

**Solid stand and comfort transportation** due to large rubber wheels and caster wheels with brakes



### Further information

Operates fully automatically

Unloader pressure switch, motor protection and on-off switch

Scope of delivery

Instruction manual

Warranty

12 months for industrial use  
24 months for private (non-commercial) use  
36 months when registered online